

Alloy Machined Side-Eject Tine - .472MT x 12.000L x .680OD



R9990040



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special highcarbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

R&R Products

RC10755

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-
	Eject
B - Tine Mounting	.472 in (11.9mm)
Dia.	
C - Tine Length	12 in (305mm)
D - Tine Tip Outside	.680 in (17.3mm)
(Hole) Dia.	
E - Tine Tip Inside	.460 in (11.7mm)
(Core) Dia.	
F - Tine Wall	.110 in (2.8mm)
Thickness	
Savings	Volume Buy

Fits Models

Redexim Verti-Drain Southern Green Soil Reliever

Amacron Golf & Turf

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON https://amacron.rrproducts.com/