



# Alloy Machined Side-Eject Tine - .375MT x 5.000L x .350OD R106-8941



## Details

Manufactured from tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

## Replaces

Toro	106-8941
------	----------

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.375 in (9.5mm)
C - Tine Length	5 in (127mm)
D - Tine Tip Outside (Hole) Dia.	.350 in (8.9mm)
E - Tine Tip Inside (Core) Dia.	.236 in (6mm)
F - Tine Wall Thickness	.049 in (1.2mm)

## Fits Models

- Toro ProCore 1298
- Toro ProCore 440
- Toro ProCore 648
- Toro ProCore 660
- Toro ProCore 864
- Toro ProCore 880
- Toro ProCore 648s

## Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>