



Alloy Hollow Side-Eject Tine - .750MT x 6.500L x .470OD R108-9162



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

| | |
|--------------|-----------|
| R&R Products | R106-8947 |
| Toro | 108-9162 |

Specifications

| | |
|----------------------------------|-------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 6.5 in (165mm) |
| D - Tine Tip Outside (Hole) Dia. | .470 in (11.9mm) |
| E - Tine Tip Inside (Core) Dia. | .300 in (7.6mm) |
| F - Tine Wall Thickness | .058 in (1.5mm) |
| Savings | Volume Buy |

Fits Models

- Toro ProCore 1298
- Toro ProCore 440
- Toro ProCore 648
- Toro ProCore 660
- Toro ProCore 864
- Toro ProCore 880

Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>



**Alloy Hollow Side-Eject Tine - .750MT x
6.500L x .470OD**
R108-9162



Toro ProCore 648s

Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>