



# Alloy Machined Side-Eject Tine - .375MT x 5.000L x .650OD R108-9294



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Replaces

Toro 108-9294

## Specifications

|                                  |                           |
|----------------------------------|---------------------------|
| Manufacturer                     | R&R Products              |
| A - Tine Type                    | Alloy Machined Side-Eject |
| B - Tine Mounting Dia.           | .375 in (9.5mm)           |
| C - Tine Length                  | 5 in (127mm)              |
| D - Tine Tip Outside (Hole) Dia. | .650 in (16.5mm)          |
| E - Tine Tip Inside (Core) Dia.  | .500 in (12.7mm)          |
| F - Tine Wall Thickness          | .065 in (1.7mm)           |
| Savings                          | Volume Buy                |

## Fits Models

Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648

## Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .375MT**  
**x 5.000L x .650OD**  
R108-9294



---

Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s

**Amacron Golf & Turf**

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>