



Rain Bird Pressure-Compensating Module - Violet 7GPH Barb x Barb

RGX71007



Details

The only emitters with self-piercing barbs, making them the easiest to install using the Xeriman tool. Widest selection of pressure-compensating emitters, with 6 flow rates and 3 inlet options. Most compact and unobtrusive emitters. Flow rates from 5 to 24 gph (18.93 to 90.84 l/h). Pressure-compensating design delivers uniform flow throughout a wide pressure range (10 to 50 psi; 0.7 to 3.5 bar). Available with 3 different inlets: Self-piercing barbs for quick one-step emitter insertion into 1/2" or 3/4" drip tubing. 10-32 threaded inlet that easily threads into a PolyFlex Riser, 1032 Thread adapter or 1800 Xeri-Bubbler Adapter. 1/2" FPT inlet that easily threads onto a 1/2" PVC riser. Robust design - durable plastic construction is UV-resistant and color-coded to identify flow rate.

Specifications

Manufacturer	Rain Bird
Manufacturer's	PC07
Model No	
Box Quantity	200
Package Quantity	1

Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>