

Alloy Machined Side-Eject Tine - .375MT x 4.500L x .320OD



RMT4940



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special highcarbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

John Deere R&R Products MT4940, TCU17452 RTCU17452

Specifications

Manufacturer A - Tine Type R&R Products Alloy Machined Side-Eject .375 in (9.5mm)

B - Tine Mounting .375 in (9.5mm)
Dia.
C - Tine Length 4.5 in (114mm)
D - Tine Tip Outside .320 in (8.1mm)
(Hole) Dia.
E - Tine Tip Inside .200 in (5mm)
(Core) Dia.
F - Tine Wall .049 in (1.2mm)
Thickness

Fits Models

John Deere Aercore 1000 John Deere Aercore 1500

Amacron Golf & Turf

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON https://amacron.rrproducts.com/





John Deere Aercore 2000 John Deere Aercore 800 Toro Greens Aerator Toro ProCore 1298 Toro ProCore 440 Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880 Toro ProCore 648s

Amacron Golf & Turf

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON https://amacron.rrproducts.com/