

Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .4250D R201509





Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products R108-9170 Toro 108-9170

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Hollow Side-Eject with Carbide Tip
B - Tine Mounting .750 in (19mm)
Dia.
C - Tine Length 4.75 in (121mm)

Carbide Tip

D - Tine Tip Outside

(Hole) Dia.

Carbide Tip

.425 in (10.7mm)

E - Tine Tip Inside .275 in (7mm)

(Core) Dia. F - Tine Wall .072 in (1.8mm)

Thickness

Fits Models

Jacobsen GA-24

Amacron Golf & Turf

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON

https://amacron.rrproducts.com/



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .4250D R201509



Ryan Greensaire II

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s