

Alloy Hollow Tine - .750MT x 5.500L x .520OD





R201586

Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Replaces

| John Deere | |
|--------------|--|
| R&R Products | |

TCU17343 RTCU17343

Specifications

| Manufacturer | R&R Products |
|----------------------|------------------|
| A - Tine Type | Alloy Hollow |
| B - Tine Mounting | .750 in (19mm) |
| Dia. | |
| C - Tine Length | 5.500 in (140mm) |
| D - Tine Tip Outside | .520 in (13.2mm) |
| (Hole) Dia. | |
| E - Tine Tip Inside | .400 in (10.2mm) |
| (Core) Dia. | |
| F - Tine Wall | .049 in (1.2mm) |
| Thickness | |

Fits Models

John Deere Aercore 1000 John Deere Aercore 1500 John Deere Aercore 2000 John Deere Aercore 800 Ryan GA30

Amacron Golf & Turf

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON https://amacron.rrproducts.com/