

Alloy Machined Side-Eject Tine - .375MT x 4.500L x .4500D



R201632



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

R&R Products R108-9105, RTCU17543 Toro 108-9105

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Machined SideEject
B - Tine Mounting .375 in (9.5mm)
Dia.

C - Tine Length 4.5 in (114mm)
D - Tine Tip Outside .450 in (11.4mm)

(Hole) Dia.

E - Tine Tip Inside .315 in (8mm)

(Core) Dia.

F - Tine Wall .065 in (1.7mm)

Thickness

Fits Models

Greencare CoreMaster John Deere Aercore 1000 John Deere Aercore 1500

Amacron Golf & Turf

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON

https://amacron.rrproducts.com/



Alloy Machined Side-Eject Tine - .375MT x 4.500L x .4500D



R201632

John Deere Aercore 2000

John Deere Aercore 800

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440 Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s

19 Tate Drive Kerang, 3579 +61 2 8011 1001 Toll Free: 1300 AMACRON

https://amacron.rrproducts.com/