



Alloy Machined Side-Eject Tine - .625MT x 6.000L x .640OD R339108



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treatment facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

Jacobsen	339108
----------	--------

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.625 in (15.9mm)
C - Tine Length	6 in (152mm)
D - Tine Tip Outside (Hole) Dia.	.640 in (16.3mm)
E - Tine Tip Inside (Core) Dia.	.500 in (12.7mm)
F - Tine Wall Thickness	.062 in (1.6mm)
Savings	Volume Buy

Fits Models

Jacobsen Aero King PT2448
Jacobsen Aero King T1224

Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .625MT
x 6.000L x .640OD
R339108**



Jacobsen Verator VA-24

Amacron Golf & Turf

19 Tate Drive Kerang, 3579

+61 2 8011 1001 Toll Free: 1300 AMACRON

<https://amacron.rrproducts.com/>